



ecoFIT Segmented Bend 1.5D 60° PE100 SDR7.4

Model:

- Long spigot for butt- and electrofusion welding
- Application: Water distribution
- Production process: segment welded
- **Derating factor 0.8 as per ISO 4427-3**
- Pressure rating: 20 bar water

d (mm)	Code	Weight (kg)	Z (mm)	L (mm)	R (mm)	e (mm)
90	P2318606090	1.49	254	150	180.0	12.3
110	P2318606110	2.65	302	200	176.0	15.1
125	P2318606125	3.53	308	200	187.5	17.1
140	P2318606140	4.58	321	200	210.0	19.2
160	P2318606160	6.25	339	200	240.0	21.9
180	P2318606180	8.40	356	200	270.0	24.6
200	P2318606200	10.80	373	200	300.0	27.4
225	P2318606225	14.46	395	200	337.5	30.8
250	P2318606250	21.13	467	250	375.0	34.2
280	P2318606280	27.97	493	250	420.0	38.3
315	P2318606315	44.60	623	350	472.5	43.1
355	P2318606355	60.01	657	350	532.5	48.5
400	P2318606400	80.31	696	350	600.0	54.7
450	P2318606450	107.82	740	350	675.0	61.5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>