




Fabricated Reducing Tee (160-500mm), PN 10, Standard PP

IR Plus/Butt Fusion

Various fittings from 250mm and up with extreme reductions cannot be performed on all machines. If unsure please contact GF representative.

d (mm)	d1 (mm)	SDR	Code	e (mm)	e1 (mm)	L (mm)	L1 (mm)
160	63	11	727 992 486	14.6	5.8	160	250
160	75	11	727 992 487	14.6	6.9	160	244
160	90	11	727 992 488	14.6	8.2	160	244
160	110	11	727 992 489	14.6	10.0	160	243
200	63	11	727 992 490	18.2	5.8	200	310
200	75	11	727 992 491	18.2	6.9	200	304
200	90	11	727 992 492	18.2	8.2	200	304
200	110	11	727 992 493	18.2	10.0	200	303
200	160	11	727 992 494	18.2	14.6	200	311
225	63	11	727 992 495	20.5	5.8	220	340
225	75	11	727 992 496	20.5	6.9	220	334
225	90	11	727 992 497	20.5	8.2	220	334
225	110	11	727 992 498	20.5	10.0	220	333
225	160	11	727 992 499	20.5	14.6	220	341
225	200	11	727 992 500	20.5	18.2	220	339
250	63	11	727 992 501	22.8	5.8	227	341
250	75	11	727 992 502	22.8	6.9	227	337
250	90	11	727 992 503	22.8	8.2	227	338
250	110	11	727 992 504	22.8	10.0	227	340
250	160	11	727 992 505	22.8	14.6	227	340
250	200	11	727 992 506	22.8	18.2	227	340
250	225	11	727 992 507	22.8	20.5	227	339
315	63	11	727 992 508	28.7	5.8	283	432
315	75	11	727 992 509	28.7	6.9	283	428
315	90	11	727 992 510	28.7	8.2	283	429
315	110	11	727 992 511	28.7	10.0	283	426
315	160	11	727 992 512	28.7	14.6	283	426
315	200	11	727 992 513	28.7	18.2	283	429
315	225	11	727 992 514	28.7	20.5	283	430
315	250	11	727 992 515	28.7	22.8	283	434
355	225	11	727 992 516	32.2	20.5	345	469
355	250	11	727 992 517	32.2	22.7	345	454
355	315	11	727 992 518	32.2	28.6	345	509
400	225	11	727 992 519	36.3	20.5	365	504
400	250	11	727 992 520	36.3	22.7	365	529
400	315	11	727 992 521	36.3	28.6	365	529
400	355	11	727 992 522	36.3	32.2	365	529
450	225	11	727 992 523	40.9	20.5	425	579
450	250	11	727 992 524	40.9	22.7	425	599
450	315	11	727 992 525	40.9	28.6	425	569
450	355	11	727 992 526	40.9	32.2	425	569
450	400	11	727 992 527	40.9	36.3	425	569
500	225	11	727 992 528	45.4	20.5	470	644
500	250	11	727 992 529	45.4	22.7	470	644
500	315	11	727 992 530	45.4	28.6	470	654
500	355	11	727 992 531	45.4	32.2	470	629
500	400	11	727 992 532	45.4	36.3	470	644
500	450	11	727 992 533	45.4	40.9	470	629

Data sheet

valid from: 4/8/25



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>