



**Angle seat check valve type 303 PVC-U
With fixed flanges JIS**

Model:

- For horizontal or vertical installation
- Leakproof even at minimum pressure
- Specific gravity of piston approx. 2 kg/dm³

DN (mm)	Size (inch)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)	EPDM Code	SP	Weight (kg)	D (mm)	D1 (mm)	D2 (mm)	D3 (mm)	H (mm)	L (mm)
15	½	10	95	161 303 117	1	0.330	95	70	48	15	65	130
20	¾	10	180	161 303 118	1	0.450	100	75	54	15	75	150
25	1	10	327	161 303 119	1	0.780	125	90	62	19	90	160
32	1 ¼	10	484	161 303 120	1	1.140	135	100	71	19	102	180
40	1 ½	10	725	161 303 121	1	1.650	140	105	88	19	123	200
50	2	10	1130	161 303 122	1	2.256	155	120	103	19	144	230
65	2 ½	10	1700	161 303 123	1	3.750	185	140	106	19	186	290
80	3	10	2500	161 303 124	1	5.070	200	150	120	19	204	310

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>