



COOL-FIT ABS Plus Installation fitting type 310 PN10

Model:

- Pre-insulated ABS metric
- Threaded outlet 1 1/4" NPSM
- Insulation made from PUR
- Outer jacket impact resistant. Color: black

Range of use:

- Compatible Signet flow sensors: type 2551, 2537, 515, 8510, 2536, 8512
- Compatible Signet pH/ORP sensors: type 2724, 2725, 2726, 2734, 2736, 2735

Attention:

- sensor length depends on installation fitting
- Connecting dimensions = Pipe inner diameter

PN (bar)	d (mm)	DN (mm)	Code	SP	Weight (lb)
10	25	20	738 310 107	1	0.831
10	32	25	738 310 108	1	0.838
10	40	32	738 310 109	1	1.089
10	50	40	738 310 110	1	1.213
10	63	50	738 310 111	1	1.548
10	75	65	738 310 112	1	1.850
10	90	80	738 310 113	1	2.125
10	110	100	738 310 114	1	2.769
10	140	125	738 310 116	1	3.971
10	160	150	738 310 117	1	5.258
10	200	200	738 310 119	1	7.225
10	225	200	738 310 120	1	11.363

Type	Sensor Type	D (mm)	H (mm)	L (mm)	z (mm)	closest inch (inch)	required Nipple
A	X0 (DN15 – DN100, 1/2" to 4")	90	78	220	110	3/4	738901107
A	X0 (DN15 – DN100, 1/2" to 4")	90	81	220	110	1	738901108
A	X0 (DN15 – DN100, 1/2" to 4")	110	84	220	110	1	738901109
A	X0 (DN15 – DN100, 1/2" to 4")	110	88	220	110	1 1/2	738901110
A	X0 (DN15 – DN100, 1/2" to 4")	125	94	220	110	2	738901111
B	X1 (DN125 – DN200, 5" to 8")	140	161	220	110	2 1/2	738901112
B	X1 (DN125 – DN200, 5" to 8")	160	171	220	110	3	738901113
B	X1 (DN125 – DN200, 5" to 8")	180	181	220	110	4	738901114
B	X1 (DN125 – DN200, 5" to 8")	225	193	220	110	5	738901116
B	X1 (DN125 – DN200, 5" to 8")	250	202	220	110	6	738901117
B	X1 (DN125 – DN200, 5" to 8")	280	211	250	125	8	738901119
B	X1 (DN125 – DN200, 5" to 8")	315	225	280	140	8	738901120

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>