



Vanne papillon type 240 PVC-C- FO (Ouverture sans pression) sans commande manuelle

Exécution:

- angle de manoeuvre 90°<
- Overall length according to EN 558, ISO 5752
- dimension de raccordement: ISO 7005 PN 10, EN 1092 PN 10, DIN 2501 PN 10, ANSI B 16.5 Class 150, BS 1560: 1958, JIS B 2220

Remarque:

For some material combination (e.g. DN300 valves with PE/PP pipes) special flange adapters are needed. Please check the "Perfect flange connection tool" on www.gfps.com

d (mm)	Pouces (inch)	DN (mm)	PN (bar)	valeur kv (Δp=1 bar) (l/min)	EPDM Code	SP	poids (kg)	FKM Code	SP	poids (kg)
63	2	50	10	740	199 240 202	1	3,439	199 240 222	1	3,443
75	2 ½	65	10	1500	199 240 203	1	3,341	199 240 223	1	3,352
90	3	80	10	2400	199 240 204	1	3,524	199 240 224	1	3,531
110	4	100	10	3800	199 240 205	1	5,357	199 240 225	1	5,371
140	5	125	10	8600	199 240 206	1	7,169	199 240 226	1	7,187
160	6	150	10	11400	199 240 207	1	10,262	199 240 227	1	10,285
225	8	200	10	19900	199 240 208	1	14,466	199 240 228	1	14,494

d (mm)	PTFE Code	poids (kg)
63	199 240 662	2,072
75	199 240 663	2,176
90	199 240 664	2,824
110	199 240 665	3,563
140	199 240 666	4,384
160	199 240 667	10,262
225	199 240 668	14,466

d (mm)	Hmax (mm)	Lmax (mm)	Wmax (mm)	U (mm)	V (mm)	H4 (mm)	V1 (mm)	Lg (mm)	D2 (mm)	Q1 (mm)	Q2 (mm)	Y (mm)	E (mm)	Y1 (mm)
63	325,3	274,4	118,4	90	133,3	23	78,8	45	104	40		98,2	70,4	15
75	338,2	274,4	132,5	90	139,9	23	85,1	46	115	54	35	98,2	70,4	15
90	362,9	325,2	136,8	90	145,6	23	91,2	49	131	67	50	111,1	83,3	15
110	386,9	359,6	161,0	90	166,4	23	105,7	56	161	88	74	114,8	87,0	
140	448,3	418,0	187,0	90	180,0	23	118,8	64	187	113	97	149,5	107,5	
160	473,0	434,0	215,0	90	189,0	23	130,9	72	215	139	123	153,1	111,1	
225	528,8	498,4	267,0	90	210,5	23	158,3	73	267	178	169	160,0	118,0	

d (mm)	M2 (mm)
63	137,2
75	137,2
90	162,6
110	179,8
140	209,0
160	217,0
225	249,2

Data sheet

valid from: 08/02/2025



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>