



Type 2552 Magmeter

Flow:

- Installs into pipe sizes: 2 to 102 in, DN50 to DN2550
- Operating range: 0.05 to 10 m/s, 0.15 to 33 ft/s
- Max Pressure rating: PP 10.3 bar @ 25 °C, 150 psi @ 77 °F
- Power source: 4 to 20mA: 21.6 to 26.4 VDC, 22.1mA max
- O-rings: FKM

MFR #	Body	Electrode	Communication Interface	Sensor Type	Mounting
3-2552-21-A-12	Stainless steel	316 SS	4-20mA	Remote Mount	9.4 in. depth
3-2552-21-B-12	Stainless steel	316 SS	4-20mA	Remote Mount	9.4 in. depth
3-2552-22-A-12	Stainless steel	316 SS	4-20mA	Remote Mount	9.4 in. depth
3-2552-22-B-12	Stainless steel	316 SS	4-20mA	Remote Mount	9.4 in. depth
3-2552-33-A-12	Stainless steel	316 SS	4-20mA	Remote Mount	14.8 in. depth
3-2552-33-B-12	Stainless steel	316 SS	4-20mA	Remote Mount	14.8 in. depth
3-2552-34-A-12	Stainless steel	316 SS	4-20mA	Remote Mount	14.8 in. depth
3-2552-34-B-12	Stainless steel	316 SS	4-20mA	Remote Mount	14.8 in. depth

MFR #	Process Connection Size (inch)	Process Connection Standard	Code
3-2552-21-A-12	1 ¼	NPT	159 001 514
3-2552-21-B-12	1 ¼	NPT	159 001 516
3-2552-22-A-12	1 ¼	ISO	159 001 518
3-2552-22-B-12	1 ¼	ISO	159 001 520
3-2552-33-A-12	1 ½	NPT	159 001 525
3-2552-33-B-12	1 ½	NPT	159 001 527
3-2552-34-A-12	1 ½	ISO	159 001 526
3-2552-34-B-12	1 ½	ISO	159 001 528

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>