



Backing flange PP-GF JIS

Model:

- Only use with flange adapter JIS
- PP-GF (30% glass-fibre reinforced)
- Connecting dimensions: JIS B 2220, 10K

AL: number of holes

d	DN	PN	Code	Weight	D	D1	D2	D3	D4	H	H1	AL	SC
(mm)	(mm)	(bar)		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)		
20	15	10	727 705 006	0.083	95	70	28	36	15	16	5	4	M12
25	20	10	727 705 007	0.101	100	75	34	43	15	18	6	4	M12
32	25	10	727 705 008	0.168	125	90	42	52	19	20	6	4	M16
40	32	10	727 705 009	0.195	135	100	51	63	19	21	7	4	M16
50	40	10	727 705 010	0.196	140	105	62	76	19	21	7	4	M16
63	50	10	727 705 011	0.228	155	120	78	92	19	21	8	4	M16
75	65	10	727 705 012	0.367	175	140	92	108	19	29	9	4	M16
90	80	10	727 705 013	0.414	185	150	110	127	19	30	10	8	M16
110	100	10	727 705 014	0.543	210	175	133	152	19	34	11	8	M16
140	125	10	727 705 016	0.880	250	210	158	191	23	41	14	8	M20
160	150	10	727 705 017	1.097	280	240	190	215	23	44	15	8	M20
225	200	10	727 705 018	2.050	340	290	238	271	23	57	20	12	M20

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>