



kraagbusafdichtingen

Uitvoering:

- For flange adaptors
- hardheid: ca. 65° shore

d (mm)	DN (mm)	EPDM code	gewicht (kg)	FKM code	gewicht (kg)	D (mm)	D1 (mm)	D2 (mm)	inch bena- dering (inch)
16	10	748 410 000	0,002	749 410 000	0,005	25,70	18,64	3,53	3/8
20	15	748 410 001	0,002	749 410 001	0,002	30,46	23,40	3,53	1/2
25	20	748 410 007	0,002	749 410 007	0,002	35,23	28,17	3,53	3/4
32	25	748 410 002	0,003	749 410 002	0,003	43,16	36,10	3,53	1
40	32	748 410 003	0,004	749 410 003	0,002	54,50	43,82	5,34	1 1/4
50	40	748 410 012	0,004	749 410 012	0,008	64,02	53,34	5,34	1 1/2
63	50	748 410 013	0,006	749 410 013	0,011	79,90	69,22	5,34	2
75	65	748 410 014	0,007	749 410 014	0,012	92,60	81,92	5,34	2 1/2
90	80	748 410 015	0,008	749 410 015	0,015	111,68	101,00	5,34	3
110	100	748 410 016	0,016	749 410 016	0,031	134,00	120,20	6,99	4
125	100	748 410 017	0,018	749 410 017	0,036	149,90	135,90	6,99	
140	125	748 410 018	0,020	749 410 018	0,039	165,80	151,80	6,99	5
160	150	748 410 019	0,025	749 410 019	0,044	184,15	170,17	6,99	6
200	200	748 410 163	0,029	749 410 163	0,048	235,60	221,60	6,99	8
225	200	748 410 022	0,034	749 410 022	0,060	254,70	240,70	6,99	8
280	250	748 410 182	0,036	749 410 182	0,066	280,10	266,10	6,99	9
250	250	748 410 173	0,042	749 410 173	0,076	305,50	291,50	6,99	10
315	300	748 410 174	0,047	749 410 174	0,083	356,30	342,30	6,99	12

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>