



Tapping Saddle with integral cutter

- Seal NBR (Nitrile Rubber) shore hardness: 60 ± 5 shore A
- Threaded outlet for PVP connections
- Parallel to main pipe
- Top saddle for solvent cement bonding

Model:

- For operating pressure up to 10bar water
- For PVC pipes

d (mm)	Code	SP	Weight (kg)	d1 (mm)	Connection	Tapping-Ø (mm)	L (mm)
63	161 112 307	1	0.890	20	1/2	21	105
63	161 112 308			25	3/4	21	105
63	161 112 309	1	1.245	32	1	30	105
90	161 112 320			20	1/2	21	105
90	161 112 321			25	3/4	21	105
90	161 112 322	1	1.384	32	1	30	105
90	161 112 325	1	1.640	63	2	39	105
110	161 112 330	1	1.481	32	3	30	105
110	161 112 331			40	1 3/4	30	105
110	161 112 332	1	1.650	50	1 1/2	39	105
110	161 112 333	1	1.943	63	2	39	105
160	161 112 354	1	1.378	32	1	30	120
160	161 112 355			40	1 1/4	30	120
160	161 112 357	1	1.739	63	2	39	120
225	161 112 370	1	2.349	32	1	30	120
225	161 112 372	0	2.650	50	1 1/2	39	120
225	161 112 373	1	2.545	63	2	39	120

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>