



ecoFIT Segmented Bend 1.5D 60° PE100 SDR7.4

Model:

- Long spigot for butt- and electrofusion welding
- Application: Water distribution
- Production process: segment welded
- **Derating factor 0.8 as per ISO 4427-3**
- Pressure rating: 20 bar water

d (mm)	Code	Weight (kg)	Z (mm)	L (mm)	R (mm)	e (mm)
90	P2318606090	1.35	228	150	135.0	12.3
110	P2318606110	2.18	245	150	165.0	15.1
125	P2318606125	2.96	259	150	187.5	17.1
140	P2318606140	3.89	271	150	210.0	19.2
160	P2318606160	5.36	289	150	240.0	21.9
180	P2318606180	9.60	406	250	270.0	24.6
200	P2318606200	12.33	423	250	300.0	27.4
225	P2318606225	16.41	445	250	337.5	30.8
250	P2318606250	21.18	467	250	375.0	34.2
280	P2318606280	27.97	492	250	420.0	38.3
315	P2318606315	41.18	573	300	472.5	43.1
355	P2318606355	64.87	708	400	532.5	48.5
400	P2318606400	86.48	746	400	600.0	54.7
450	P2318606450	115.72	790	400	675.0	61.5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>