



Installation fitting type 310 PVC-U For socket systems BS

Model:

- Material: PVC-U
- Threaded outlet 1 ¼" NPSM
- Union end with solvent cement socket PVC-U

Range of use:

- Compatible Signet flow sensors: type 2551, 2537, 515, 8510, 2536, 8512
- Compatible Signet pH/ORP sensors: type 2724, 2725, 2726, 2734, 2736, 2735

Attention:

- sensor length depends on installation fitting

| DN (mm) | Size (inch) | PN (bar) | Type | EPDM Code | SP | Weight (kg) | FKM Code | SP | Weight (kg) |
|------------|----------------|-------------|---------|--------------------|----|----------------|--------------------|----|----------------|
| 15 | ½ | 15 | PVAT005 | 721 310 306 | 1 | 0.181 | 721 310 336 | 1 | 0.181 |
| 20 | ¾ | 15 | PVAT007 | 721 310 307 | 1 | 0.244 | 721 310 337 | 1 | 0.244 |
| 25 | 1 | 15 | PVAT010 | 721 310 308 | 1 | 0.333 | 721 310 338 | 1 | 0.299 |
| 32 | 1 ¼ | 15 | PVAT012 | 721 310 309 | 1 | 0.403 | 721 310 339 | 1 | 0.440 |
| 40 | 1 ½ | 15 | PVAT015 | 721 310 310 | 1 | 0.700 | 721 310 340 | 1 | 0.579 |
| 50 | 2 | 15 | PVAT020 | 721 310 311 | 1 | 1.011 | 721 310 341 | 1 | 1.011 |

| DN (mm) | L (mm) | L1 (mm) | D (mm) | H (mm) | z (mm) | Sensor Type |
|------------|-----------|------------|-----------|-----------|-----------|----------------|
| 15 | 131 | 90 | 43 | 76 | 48 | flow X0, pH XX |
| 20 | 147 | 100 | 51 | 78 | 53 | flow X0, pH XX |
| 25 | 164 | 110 | 58 | 81 | 58 | flow X0, pH XX |
| 32 | 171 | 110 | 72 | 85 | 58 | flow X0, pH XX |
| 40 | 188 | 120 | 83 | 89 | 63 | flow X0, pH XX |
| 50 | 211 | 130 | 100 | 95 | 68 | flow X0, pH XX |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>