



**SYGEF Plus Flare transition fitting**  
**PN10**  
**High Purity clean-room product ISO Class 5 (100)**

**Model:**

- All articles can be welded to SYGEF SDR21/PN16 pipes and fittings
- Material: PVDF-HP

d	DN	tube size	PN	SDR	FM	Code	Weight	L	L1	L2	D	e
(mm)	(mm)	(inch)	(bar)				(kg)	(mm)	(mm)	(mm)	(mm)	(mm)
20	15	¼	10	33	BCF, IR	<b>735 598 430</b>	0.028	75	45	30	21	1.9
20	15	⅜	10	33	BCF, IR	<b>735 598 431</b>	0.022	76	46	30	23	1.9
20	15	½	10	33	BCF, IR	<b>735 598 432</b>	0.034	77	47	30	26	1.9
20	15	¾	10	33	BCF, IR	<b>735 598 433</b>	0.043	78	48	30	34	1.9
25	20	¼	10	33	BCF, IR	<b>735 598 435</b>	0.033	75	45	30	21	1.9
25	20	⅜	10	33	BCF, IR	<b>735 598 436</b>	0.025	76	46	30	23	1.9
25	20	½	10	33	BCF, IR	<b>735 598 437</b>	0.028	77	47	30	26	1.9
25	20	¾	10	33	BCF, IR	<b>735 598 438</b>	0.050	78	48	30	34	1.9
25	20	1	10	33	BCF, IR	<b>735 598 439</b>	0.102	87	57	30	46	1.9
32	25	½	10	33	BCF, IR	<b>735 598 442</b>	0.036	77	47	30	26	2.4
32	25	¾	10	33	BCF, IR	<b>735 598 443</b>	0.048	78	48	30	34	2.4
32	25	1	10	33	BCF, IR	<b>735 598 444</b>	0.107	87	57	30	46	2.4

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:  
 info.ps@georgfischer.com Internet: <http://www.gfps.com>