



PROGEF Plus Reducer SDR11/PN10

Model:

- Cleaned and double bagged
- Conventional butt-welding according to DVS 2207
- IR = Infrared welding compatible
- Material: PP-H

d	d1	PN	FM	Code	Weight	L	L1	L2	e	e1
(mm)	(mm)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)	(mm)
25	20	10	IR	727 908 637	0.008	50	20	20	2.3	1.9
32	20	10	IR	727 908 642	0.012	50	20	20	2.9	1.9
32	25	10	IR	727 908 641	0.013	50	20	20	2.9	2.3
40	20	10	IR	727 908 648	0.015	58	20	23	3.7	1.9
40	25	10	IR	727 908 647	0.017	55	20	20	3.7	2.3
40	32	10	IR	727 908 646	0.019	55	20	20	3.7	2.9
50	25	10	IR	727 908 654	0.026	60	20	20	4.6	2.3
50	32	10	IR	727 908 653	0.026	60	20	20	4.6	2.9
50	40	10	IR	727 908 652	0.032	60	20	20	4.6	3.7
63	32	10	IR	727 908 660	0.046	65	20	20	5.8	2.9
63	40	10	IR	727 908 659	0.048	65	20	20	5.8	3.7
63	50	10	IR	727 908 658	0.051	65	20	20	5.8	4.6
75	40	10	IR	727 908 666	0.063	68	20	20	6.8	3.7
75	50	10	IR	727 908 665	0.072	65	20	20	6.8	4.6
75	63	10	IR	727 908 664	0.079	65	20	20	6.8	5.8
90	63	10	IR	727 908 671	0.119	75	22	19	8.2	5.8
90	75	10	IR	727 908 670	0.131	75	21	19	8.2	6.8
110	63	10	IR	727 908 672	0.201	90	28	28	10.6	6.2
110	75	10	IR	727 908 677	0.211	90	28	18	10.0	6.8
110	90	10	IR	727 908 676	0.231	90	28	20	10.0	8.2
125	110	10	IR	727 908 680	0.325	100	31	30	11.4	10.0
140	110	10	IR	727 908 685	0.430	110	33	29	12.7	10.0
140	125	10	IR	727 908 684	0.468	110	34	30	12.7	11.4
160	110	10	IR	727 908 690	0.595	120	38	27	14.6	10.0
160	140	10	IR	727 908 688	0.652	120	40	35	14.6	12.7
180	90	10	IR	727 908 780	0.800	145	50	40	16.4	8.2
180	110	10	IR	727 908 781	1.010	150	50	40	16.4	10.0
180	125	10	IR	727 908 782	0.985	145	52	40	16.4	11.4
180	140	10	IR	727 908 783	0.995	135	51	47	16.4	12.7
180	160	10	IR	727 908 784	1.020	135	55	52	16.4	14.6
200	160	10	IR	727 908 692	1.120	145	50	40	18.2	14.6
200	180	10	IR	727 908 785	1.300	145	50	45	18.2	16.4
225	110	10	IR	727 908 695	1.489	160	55	35	20.5	10.0
225	160	10	IR	727 908 696	1.590	160	55	40	20.5	14.6
225	180	10	IR	727 908 786	1.770	163	60	58	20.5	16.4
225	200	10	IR	727 908 697	1.650	160	55	50	20.5	18.2
250	160	10	IR	727 908 787	2.140	170	63	53	22.7	14.6
250	225	10	IR	727 908 788	2.750	180	65	65	22.7	20.5
280	225	10	IR	727 908 789	3.425	203	72	57	25.4	20.5
280	250	10	IR	727 908 790	1.980	206	75	60	25.4	22.7
315	225	10	IR	727 908 791	5.110	237	84	60	28.6	20.5
315	250	10	IR	727 908 792	5.105	231	86	63	28.6	22.7
315	280	10	IR	727 908 793	5.130	222	80	70	28.6	25.4

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Data sheet

valid from: 4/30/25



Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>