



PROGEF Standard Ball Valve type 546 Pro

Oil-free


With fusion sockets PP-H ISO

Model:


- Lockable lever as standard
- Ball seals PTFE
- Integrated stainless steel mounting inserts
- Z-dimension, valve end and union nut **are compatible** with type 546 (1st Generation)

Option:

- Interface module for position feedback sensor with LED (PNP, NPN and NAMUR)
- Manual spring return lever ("Dead man") (DN10-25)
- Pneumatic or electric actuators from GF
- Individual configuration of the valve possible



d (mm)	DN (mm)	Size (inch)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)	EPDM Code	SP	Weight (kg)	FKM Code	SP	Weight (kg)
20	15	½	10	185	167 546 902	1	0.119	167 546 912	1	0.115
25	20	¾	10	350	167 546 903	1	0.183	167 546 913	1	0.184
32	25	1	10	700	167 546 904	1	0.258	167 546 914	1	0.260
40	32	1 ¼	10	1000	167 546 905	1	0.440	167 546 915	1	0.440
50	40	1 ½	10	1600	167 546 906	1	0.610	167 546 916	1	0.620
63	50	2	10	3100	167 546 907	1	1.113	167 546 917	1	1.145
75	65	2 ½	10	5000	167 546 908	1	3.700	167 546 918	1	3.700
90	80	3	10	7000	167 546 909	1	5.500	167 546 919	1	5.500
110	100	4	10	11000	167 546 910	1	8.700	167 546 920	1	8.700



d (mm)	B3 (mm)	DE1 (mm)	G (inch)	H (mm)	H1 (mm)	H4 (mm)	L (mm)	Lz (mm)	M (mm)	M1 (mm)	M2 (mm)	z (mm)
20	25	50	M6	60.5	27	12	95	28	82	35	47	66
25	25	58	M6	74.0	30	12	109	33	106	44	62	77
32	25	68	M6	80.0	36	12	119	36	106	44	62	83
40	45	84	M8	95.0	44	15	135	43	131	57	74	99
50	45	97	M8	101.5	51	15	147	45	131	57	74	105
63	45	124	M8	116.5	64	15	168	51	152	66	86	117
75	70	166	M8	169.0	85	15	233	68	270	64	205	167
90	70	200	M8	180.0	105	15	254	71	270	64	205	180
110	120	238	M12	194.0	123	22	301	82	326	71	255	215

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>