





Ball valve type 375 PVC-C

With solvent cement sockets Inch ASTM/Inclusive 2 threaded valve ends NPT

Model:

- True double union safe block ball valve
- Ball seat PTFE
- Handle includes integrated tool for ball seat adjustment
- Very compact dimensions
- z-dimension, valve end and union nut are not compatible with type 546
- Combo valve ends reduce stock positions

Range of use:

- Basic industrial applications without automation

DN (mm)	Size (inch)	PN (bar)	EPDM Code	SP	Weight (kg)	FKM Code
15	½	16	163 375 002	1	0.175	163 375 017
20	¾	16	163 375 003	1	0.269	163 375 018
25	1	16	163 375 004	1	0.389	163 375 019
32	1 ¼	16	163 375 005	1	0.568	163 375 020
40	1 ½	16	163 375 006	1	0.928	163 375 021
50	2	16	163 375 007	1	1.550	163 375 022
65	2 ½	10	163 375 008	1	2.190	163 375 023
80	3	10	163 375 009	1	3.360	163 375 024
100	4	10	163 375 010	1	6.060	163 375 025

D (mm)	H (mm)	L (mm)	L1 (mm)	L2 (mm)	L3 (mm)	z (mm)
50	53	79	67	42	40	48
59	60	92	77	48	45	53
68	67	105	87	54	51	58
80	79	120	102	62	59	68
94	90	126	119	72	70	78
115	107	150	146	86	84	93
145	129	206	179	110	103	118
168	143	242	209	128	120	140
210	169	282	250	150	141	160

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>