




3-Way ball valve type 170 PVC-U
Vertical/L-port 100-230V
With manual emergency override
With solvent cement sockets metric



Model:

- Voltage 100-230V, 50-60Hz
- Integrated stainless steel mounting inserts



Option:

- Fail-safe return unit, Monitoring board, Position controller, Profibus DP board

d	DN	PN	EA	EPDM	weight
(mm)	(mm)	(bar)		Code	(lb)
16	10	10	EA25	199 170 242	4.495
20	15	10	EA25	199 170 243	4.504
25	20	10	EA25	199 170 244	4.740
32	25	10	EA25	199 170 245	4.998
40	32	10	EA25	199 170 246	5.631
50	40	10	EA25	199 170 247	7.061
63	50	10	EA25	199 170 248	8.768



d	D	H	H1	H2	H3	H5	L	L1	L2	L5	L6	L7	L8	z	closest
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	inch
16	50	231	62	64	94	167	92	180	56	97	83	122	33	64	3/8
20	50	231	62	64	94	167	95	180	56	97	83	122	33	64	1/2
25	58	240	72	73	94	167	111	180	66	97	83	122	33	74	3/4
32	68	240	77	73	94	167	123	180	71	97	83	122	33	79	1
40	84	251	87	84	94	167	146	180	85	97	83	122	33	95	1 1/4
50	97	251	97	84	94	167	157	180	89	97	83	122	33	95	1 1/2
63	124	273	112	106	94	167	183	180	101	97	83	122	33	107	2



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Data sheet

valid from: 9/13/22



Internet: <http://www.gfps.com>