

Løslens PVC-U

Modell


- For muffesystem metrisk og BS
- Metrisk: ISO 7005, EN 1092, ISO 9624
- ASME: ANSI/ASME B 16.5 class 150, ASTM D2024, BS 1560, BS EN 1759
- Maks medie eller omgivende temperatur 45°C

AL: Antall hull

¹⁾ Ikke for BS

	d (mm)	DN Størrelse (mm)	PN (inch)	Standard (bar)	Bolt circle	Design
	16	10	3/8	10	Metrisk	PN10 Muffe
	20	15	1/2	10	Metrisk	PN10 Butt/Muffe
	25	20	3/4	10	Metrisk	PN10 Butt/Muffe
	32	25	1	10	Metrisk	PN10 Butt/Muffe
	40	32	1 1/4	10	Metrisk	PN10 Butt/Muffe
	50	40	1 1/2	10	Metrisk	PN10 Butt/Muffe
	63	50	2	10	Metrisk	PN10 Butt/Muffe
	75	65	2 1/2	10	Metrisk	PN10 Butt/Muffe
	90	80	3	10	Metrisk	PN10 Muffe
	110	100	4	10	ASME	class 150 Muffe
1	110	100	4	10	Metrisk	PN10 Muffe
	125	125	4 1/2	10	Metrisk	PN10 Muffe
	140	125	5	10	Metrisk	PN10 Muffe
1	160	150	6	10	Metrisk	PN10 Muffe
	200	200	7	10	Metrisk	PN10 Muffe
	225	200	8	10	Metrisk	PN10 Muffe
	250	250	9	6	Metrisk	PN10 Muffe
	250	225	9	6	Metrisk	PN10 Muffe
	280	250	10	6	Metrisk	PN10 Muffe
	315	300	12	6	Metrisk	PN10 Muffe
	355	350	14	6	Metrisk	PN10 Muffe
	400	400	16	6	Metrisk	PN10 Muffe
	20	15	1/2	10	ASME	class 150 Muffe
	25	20	3/4	10	ASME	class 150 Muffe
	32	25	1	10	ASME	class 150 Muffe
	40	32	1 1/4	10	ASME	class 150 Muffe
	50	40	1 1/2	10	ASME	class 150 Muffe
	63	50	2	10	ASME	class 150 Muffe
	75	65	2 1/2	10	ASME	class 150 Muffe
	90	80	3	10	ASME	class 150 Muffe
	110	100	4	10	ASME	class 150 Muffe
	140	125	5	10	ASME	class 150 Muffe
	160	150	6	10	ASME	class 150 Muffe
	225	200	8	10	ASME	class 150 Muffe

	Kode	NRF	SP	Vekt (kg)	D (mm)	D1 (mm)	D2 (mm)	D3 (mm)	H (mm)	r (mm)	AL	SC
	721 700 005	239 86 36	100	0,053	90	60	23	14	10	1	4	M12
	721 700 006	239 86 37	90	0,067	95	65	28	14	11	1	4	M12
	721 700 007	239 86 38	50	0,092	105	75	34	14	12	2	4	M12
	721 700 008	239 86 39	40	0,133	115	85	42	14	14	2	4	M12
	721 700 009	239 86 41	25	0,198	140	100	51	18	15	2	4	M16
	721 700 010	239 86 42	20	0,247	150	110	62	18	16	2	4	M16
	721 700 011	239 86 43	30	0,312	165	125	78	18	18	3	4	M16
	721 700 012	239 86 44	25	0,376	185	145	92	18	19	3	4	M16
	721 700 013	239 86 45	20	0,464	200	160	110	18	20	3	8	M16
	161 483 180		30	0,538	220	190	133	19	22	3	8	
1	721 700 014	239 86 46	30	0,543	220	180	133	18	22	3	8	M16
	721 700 015	239 86 47	12	0,904	250	210	150	18	26	5	8	M16



	Kode	NRF	SP	Vekt (kg)	D (mm)	D1 (mm)	D2 (mm)	D3 (mm)	H (mm)	r (mm)	AL	SC
1	721 700 016	239 86 48	12	0,758	250	210	167	18	26	4	8	M16
	721 700 017	239 86 49	5	1,009	285	240	190	22	28	4	8	M20
	721 700 019	239 86 51	8	1,669	340	295	226	22	32	4	8	M20
	721 700 020	239 86 52	8	1,377	340	295	250	22	32	4	8	M20
	721 700 021	239 86 53	1	2,376	395	350	277	22	36	4	12	M20
	721 700 136	239 86 54	1	1,800	370	325	277	22	36	4	8	M20
	721 700 137	239 86 55	1	1,746	395	350	310	22	36	4	12	M20
	721 700 138	239 86 56	1	2,349	445	400	348	22	36	4	12	M20
	721 700 139	239 86 57	1	3,485	505	460	388	22	38	5	16	M20
	721 700 140	239 86 58	1	4,526	565	515	442	26	42	5	16	M24
	721 702 206		90	0,068	95	60	28	16	11	1	4	
	721 702 207		50	0,090	105	70	34	16	12	2	4	
	721 702 208		40	0,128	115	79	42	16	14	2	4	
	721 702 209		25	0,203	140	89	51	16	15	2	4	
	721 702 210		20	0,238	150	98	62	16	16	2	4	
	721 702 211		30	0,302	165	121	78	19	18	3	4	
	721 702 212		27	0,369	185	140	92	19	19	3	4	
	721 702 213		20	0,509	200	152	110	19	20	3	4	
	721 702 214		30	0,516	220	190	138	19	22	3	8	
	721 702 216		12	0,737	250	216	167	22	26	4	8	
	721 702 217		5	1,910	285	241	200	22	28	4	8	
	721 702 220		8	1,360	340	298	250	22	32	4	8	

De tekniske data er uforpliktende. De er hverken uttrykk for garanterte egenskaper, funksjoner eller for garantert holdbarhet. Rett til endringer forbeholdes. Våre generelle salgsbetingelser er gjeldene.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>