


Ball valve type 542 PP-H
With threaded socket (NPT)

Model:

- For easy installation and removal
- Ball seals PTFE/ red lever

Option:

- Individual configuration of the valve possible
- Assembling of a valve tag possible



d	DN	Size	PN	Cv-value	EPDM	SP	weight	FKM	SP	weight
(mm)	(mm)	(inch)	(bar)	(l/min)	Code		(kg)	Code		(kg)
16	10	3/8	10	71	167 542 321	1	0.120	167 542 331	1	0.120
20	15	1/2	10	185	167 542 322	1	0.128	167 542 332	1	0.128
25	20	3/4	10	350	167 542 323	1	0.180	167 542 333	1	0.180
32	25	1	10	700	167 542 324	1	0.270	167 542 334	1	0.270
40	32	1 1/4	10	1000	167 542 325	1	0.460	167 542 335	1	0.460
50	40	1 1/2	10	1600	167 542 326	1	0.635	167 542 336	1	0.635
63	50	2	10	3100	167 542 327	1	1.204	167 542 337	1	1.204

d	D	H	L	L1	L2	L5	L6	z
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
16	50	54	96	72	56	26	46	70
20	50	54	99	72	56	26	46	66
25	58	66	111	93	65	34	59	78
32	68	71	127	93	71	34	59	86
40	84	85	147	110	85	41	69	103
50	97	92	157	110	89	41	69	113
63	124	108	184	128	101	49	79	138

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>