


overgangsmof PE/staal (RVS 1.4305), binnendraad met geïntegreerde kleminrichting



- 10 bar gas / 16 bar water
- met geïntegreerde kleminrichting
- 4 mm stekkeraansluiting
- begrensd lasindicator
- wordt geleverd als kit



d	Thread Type	Inch	DN	PN	code	gewicht	Do	Lmax	P1	SLW	SDR pipe
(mm)		(inch)	(mm)	(bar)		(kg)	(mm)	(mm)	(mm)	(mm)	
20	Rp	½	15	16	724 920 256	0,179	31	100	34	30	9-11
25	Rp	¾	20	16	724 920 257	0,231	36	101	34	35	9-11
32	Rp	1	25	16	724 920 258	0,319	44	108	34	40	9-11
40	Rp	1 ¼	32	16	724 920 259	0,480	54	118	39	50	9-11
50	Rp	1 ½	40	16	724 920 260	0,646	66	126	43	60	9-11
63	Rp	2	50	16	724 920 261	0,931	81	138	46	70	9-17.6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>