



ecoFIT Segmented Bend 1.5D 90° PE100 SDR9 PN20

Model:

- Long spigot for butt- and electrofusion welding
- Application: Water distribution
- Production process: segment welded
- **Derating factor 0.8 as per ISO 4427-3**
- Pressure rating: 16 bar water

Note:

* Please call us for availability

d	Code	Weight	Z	L	R	e	
(mm)		(kg)	(mm)	(mm)	(mm)	(mm)	
90	P2317607090	1.58	348	150	198.0	10.1	
110	P2317607110	2.88	420	200	220.0	12.3	
125	P2317607125	3.72	425	200	225.0	14.0	
140	P2317607140	4.67	424	200	224.0	15.7	
160	P2317607160	6.33	448	200	240.0	17.9	
180	P2317607180	8.52	473	200	270.0	20.1	
200	P2317607200	11.17	502	200	300.0	22.4	
225	P2317607225	14.89	537	200	337.5	25.2	
250	P2317607250	21.71	622	250	375.0	27.9	
280	P2317607280	28.78	663	250	420.0	31.3	
315	P2317607315	45.50	821	350	472.5	35.2	
355	P2317607355	61.25	883	350	532.5	39.7	
400	P2317607400	83.41	950	350	600.0	44.7	
450	P2317607450	113.12	1025	350	675.0	50.3	
*	500	P2317607500	157.74	1150	400	750.0	55.8
*	560	P2317607560	210.59	1240	400	840.0	62.5
*	630	P2317607630	300.29	1395	450	945.0	70.3

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>