



PROGEF Natural valve end 546 SDR11/PN10

Model:

- Material: PP-R unpigmented
- Bead and Crevice Free weldable with the new BCF® Plus fusion machine
- Infrared-(IR Plus®) compatible. Choose fusion parameters: PP-n (PP-R)
- Conventional butt-welding according to DVS 2207

d (mm)	FM	Code	Weight (kg)	L (mm)	L1 (mm)	L2 (mm)	D (mm)	e (mm)
20	BCF, IR	168 480 260	0.007	37	4	25	38	1.9
25	BCF, IR	168 480 261	0.011	39	5	25	44	2.3
32	BCF, IR	168 480 262	0.018	40	5	25	53	2.9
40	BCF, IR	168 480 263	0.029	43	5	25	65	3.7
50	BCF, IR	168 480 264	0.053	51	6	25	77	4.6
63	BCF, IR	168 480 265	0.093	60	7	28	99	5.8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>