



Data sheet

valid from: 4/22/25



COOL-FIT 4.0 Pipe d32-d450

Model:

- Pre-insulated PE100 SDR11/17 metric
- Insulation made from GF HE foam
- Impact resistant. Color: black
- Length: 5m for d32-d225, 5.9m for d250-d450
- With free ends for electrofusion

Note:

Peeling of free ends necessary for dimensions d250 - d450

d (mm)	D (mm)	DN (mm)	SDR	PN (bar)	Code	Weight (kg/m)	di (mm)	L (mm)	L1 (mm)	closest inch (inch)
32	90	25	11	16	738 173 108	1.411	26.2	5000	36	1
40	110	32	11	16	738 173 109	2.054	32.6	5000	40	1 ¼
50	110	40	11	16	738 173 110	2.221	40.8	5000	44	1 ½
63	125	50	11	16	738 173 111	2.987	51.4	5000	48	2
75	140	65	11	16	738 173 112	3.757	61.4	5000	55	2 ½
90	160	80	11	16	738 173 113	4.819	73.6	5000	62	3
110	180	100	11	16	738 173 114	6.200	90.0	5000	72	4
140	225	125	11	16	738 173 116	9.676	114.6	5000	84	5
160	250	150	17	10	738 173 117	9.921	141.0	5000	90	6
225	315	200	17	10	738 173 120	16.620	198.2	5000	110	8
250	355	250	17	10	738 173 021	18.180	220.4	5900	123	10
280	400	250	17	10	738 173 022	22.640	246.8	5900	126	10
315	450	300	17	10	738 173 023	28.510	277.6	5900	133	12
355	500	350	17	10	738 173 024	35.350	312.8	5900	148	14
400	560	400	17	10	738 173 125	44.070	352.6	5900	150	16
450	630	450	17	10	738 173 126	55.490	396.6	5900	165	18

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>