




**PRIMOFIT Coupling short galvanised
equal for PE/PE-Xa pipe to steel pipe**

including insert stiffener
*** according to EN 1555-2



| | Dim. PE (mm) | Dim. St (inch) | NBR Code | SP | GP | Weight (kg) | EPDM Code | GP | Weight (kg) |
|-----|-----------------|-------------------|--------------------|----|----|----------------|--------------------|----|----------------|
| | 20 x 3,0 | ½ | 775 102 701 | 1 | 20 | 0.378 | | | |
| | 25 x 3,5 | ¾ | 775 102 702 | 1 | 5 | 0.403 | | | |
| | 32 x 4,4 | 1 | 775 102 703 | 1 | 15 | 0.632 | | | |
| | 40 x 5,5 | 1 ¼ | 775 102 704 | 1 | 10 | 0.760 | | | |
| | 50 x 6,9 | 1 ½ | 775 102 705 | 1 | 5 | 0.900 | | | |
| | 63 x 8,6 | 2 | 775 102 706 | 1 | 5 | 1.680 | | | |
| | 20 x 2,0 | ½ | 775 102 501 | 1 | 20 | 0.363 | 775 106 501 | 20 | 0.363 |
| | 25 x 2,3 | ¾ | 775 102 502 | 1 | 20 | 0.408 | 775 106 502 | 20 | 0.450 |
| *** | 25 x 3,0 | ¾ | 775 102 442 | 1 | 20 | 0.408 | | | |
| | 32 x 3,0 | 1 | 775 102 503 | 1 | 15 | 0.595 | 775 106 503 | 15 | 0.533 |
| | 40 x 3,7 | 1 ¼ | 775 102 504 | 1 | 10 | 0.760 | 775 106 504 | 10 | 0.760 |
| | 50 x 4,6 | 1 ½ | 775 102 505 | 1 | 5 | 0.920 | 775 106 505 | 5 | 0.920 |
| | 63 x 5,8 | 2 | 775 102 506 | 1 | 5 | 1.700 | 775 106 506 | 5 | 1.700 |
| | 25 x 2,0 | ¾ | 775 102 602 | 1 | 20 | 0.462 | | | |
| *** | 25 x 2,3 | ¾ | 775 102 452 | 1 | 20 | 0.462 | | | |
| | 32 x 2,0 | 1 | 775 102 603 | 1 | 15 | 0.644 | | | |
| *** | 32 x 2,3 | 1 | 775 102 453 | 1 | 15 | 0.644 | | | |
| | 40 x 2,3 | 1 ¼ | 775 102 604 | 1 | 10 | 0.770 | | | |
| | 50 x 2,9 | 1 ½ | 775 102 605 | 1 | 5 | 0.900 | | | |
| | 63 x 3,6 | 2 | 775 102 606 | 1 | 5 | 1.836 | | | |

| | Dim. PE (mm) | Dim. St (inch) | D (mm) | L (mm) | x PE (mm) | x St (mm) |
|-----|-----------------|-------------------|-----------|-----------|--------------|--------------|
| | 20 x 3,0 | ½ | 45 | 85 | 31 - 33 | 30 - 34 |
| | 25 x 3,5 | ¾ | 51 | 89 | 31 - 33 | 30 - 34 |
| | 32 x 4,4 | 1 | 59 | 95 | 31 - 33 | 30 - 34 |
| | 40 x 5,5 | 1 ¼ | 68 | 96 | 32 - 38 | 30 - 36 |
| | 50 x 6,9 | 1 ½ | 75 | 103 | 35 - 43 | 32 - 38 |
| | 63 x 8,6 | 2 | 96 | 113 | 39 - 47 | 36 - 42 |
| | 20 x 2,0 | ½ | 45 | 85 | 31 - 33 | 30 - 34 |
| | 25 x 2,3 | ¾ | 51 | 89 | 31 - 33 | 30 - 34 |
| *** | 25 x 3,0 | ¾ | 51 | 89 | 31 - 33 | 30 - 34 |
| | 32 x 3,0 | 1 | 59 | 95 | 31 - 33 | 30 - 34 |
| | 40 x 3,7 | 1 ¼ | 68 | 96 | 32 - 38 | 30 - 36 |
| | 50 x 4,6 | 1 ½ | 75 | 103 | 35 - 43 | 32 - 38 |
| | 63 x 5,8 | 2 | 96 | 113 | 39 - 47 | 36 - 42 |
| | 25 x 2,0 | ¾ | 51 | 89 | 31 - 33 | 30 - 34 |
| *** | 25 x 2,3 | ¾ | 51 | 89 | 31 - 33 | 30 - 34 |
| | 32 x 2,0 | 1 | 59 | 95 | 31 - 33 | 30 - 34 |
| *** | 32 x 2,3 | 1 | 59 | 95 | 31 - 33 | 30 - 34 |
| | 40 x 2,3 | 1 ¼ | 68 | 96 | 32 - 38 | 30 - 36 |
| | 50 x 2,9 | 1 ½ | 75 | 103 | 35 - 43 | 32 - 38 |
| | 63 x 3,6 | 2 | 96 | 113 | 39 - 47 | 36 - 42 |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Data sheet

valid from: 7/29/25



Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>