



ecoFIT Reducer Eccentric Short Spigot PE100 SDR9

Model:

- Short spigot for butt welding
- Application: Water distribution
- Pressure rating: 20 bar water

Note:

Please call us for availability of other sizes and dimensions

d	d1	Code	Weight	z	L	L1	e	e1
(mm)	(mm)		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)
90	63	P2317112092	0.17	100	40	30	10.1	7.1
90	75	P2317112091	0.18	100	40	30	10.1	8.4
110	75	P2317112112	0.26	100	40	30	12.3	8.4
110	90	P2317112111	0.27	100	40	30	12.3	10.1
125	90	P2317112127	0.34	100	40	30	14.0	10.1
125	110	P2317112126	0.36	100	40	30	14.0	12.3
140	110	P2317112142	0.44	100	40	30	15.7	12.3
140	125	P2317112141	0.45	100	40	30	15.7	14.0
160	125	P2317112162	0.58	100	40	30	17.9	14.0
160	140	P2317112161	0.59	100	40	30	17.9	15.7
180	140	P2317112182	0.74	100	40	30	20.1	15.7
180	160	P2317112181	0.75	100	40	30	20.1	17.9
200	160	P2317112202	1.36	120	50	30	22.4	17.9
200	180	P2317112201	1.12	120	50	30	22.4	20.1
225	180	P2317112227	1.40	120	50	30	25.2	20.1
225	200	P2317112226	1.42	120	50	30	25.2	22.4
250	200	P2317112252	1.74	120	50	30	27.9	22.4
250	225	P2317112251	1.75	120	50	30	27.9	25.2
280	225	P2317112282	2.22	120	50	30	31.3	25.2
280	250	P2317112281	2.21	120	50	30	31.3	27.9
315	250	P2317112317	3.46	150	60	40	35.2	27.9
315	280	P2317112316	3.47	150	60	40	35.2	31.3
355	280	P2317112357	4.46	150	60	40	39.7	31.3
355	315	P2317112356	4.44	150	60	40	39.7	35.2
400	315	P2317112402	5.76	150	60	40	44.7	35.2
400	355	P2317112401	5.67	150	60	40	44.7	39.7

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>