Data sheet

valid from: 5/16/25





Pipe PVC-U transparent SDR13,6/Series S6,3

Model:

- Material: PVC-UDimension: acc. to DIN 8062
- Colour: transparent Transparency depends on outer diameter and wall thickness! Chemical and thermical stress can cause discolouration
- Pipe length: 5000mm, with plain ends
- Food grade, with declaration of conformity acc. EU 10/2011 and EU 1953/2004
- Attention: Pressure rates refer to operating temperatures at 20°C. Higher temperatures and
 aggressive flow media reduce pressure load (see above DIN and our technical documentation).
 Pressure load capacity has to be determined in consideration with safety demands of the respective applications and calculated in accordance.
- * SDR 11

	Required quantity clo- sures per piece [pieces]	d (mm)	SDR	PN (bar)	Code	Weight (kg∕m)	di (mm)	e (mm)
* 20	20	12	11	16	192 017 104	0.062	10.0	1.1
* 20	20	16	13.6	16	192 017 105	0.091	13.6	1.2
* 20	20	20	13.6	16	192 017 106	0.139	17.0	1.5
* 20	20	25	13.6	16	192 017 107	0.215	21.2	1.9
* 10	10	32	13.6	16	192 017 108	0.347	27.2	2.4
* 5	5	40	13.6	16	192 017 109	0.533	34.0	3.0
* 5	5	50	13.6	16	192 017 110	0.821	42.6	3.7
* 3	3	63	13.6	16	192 017 111	1.310	53.6	4.7

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com