




## 90° 变径三通 PE100 SDR17

### 型号:

- 水16bar , 气10bar
- Fittings are injection moulded

| d    | d2   | DN   | PN | code        | weight | L2   | Lmax | Q1   | Q2   | s1   | s2   |
|------|------|------|----|-------------|--------|------|------|------|------|------|------|
| (mm) | (mm) | (mm) |    |             | (kg)   | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) |
| 90   | 50   | 80   | 10 | 753 201 827 | 0,630  | 117  | 275  | 79   | 55   | 5,4  | 3,0  |
| 90   | 63   | 80   | 10 | 753 200 829 | 0,560  | 123  | 275  | 79   | 63   | 5,4  | 3,8  |
| 90   | 75   | 80   | 10 | 753 201 855 | 0,580  | 132  | 286  | 80   | 75   | 5,4  | 4,5  |
| 110  | 63   | 100  | 10 | 753 200 828 | 1,010  | 147  | 318  | 82   | 63   | 6,6  | 3,8  |
| 110  | 75   | 100  | 10 | 753 200 131 | 1,029  | 155  | 324  | 85   | 74   | 6,6  | 4,5  |
| 110  | 90   | 100  | 10 | 753 200 832 | 0,941  | 158  | 318  | 82   | 79   | 6,6  | 5,4  |
| 125  | 90   | 100  | 10 | 753 200 132 | 1,500  | 165  | 354  | 90   | 82   | 7,4  | 5,4  |
| 125  | 110  | 100  | 10 | 753 200 133 | 1,560  | 167  | 354  | 90   | 85   | 7,4  | 6,6  |
| 160  | 63   | 150  | 10 | 753 200 834 | 2,554  | 130  | 330  | 86   | 63   | 9,5  | 3,8  |
| 160  | 75   | 150  | 10 | 753 200 880 | 1,920  | 180  | 420  | 105  | 75   | 9,5  | 4,5  |
| 160  | 90   | 150  | 10 | 753 200 836 | 1,972  | 188  | 410  | 98   | 79   | 9,5  | 5,4  |
| 160  | 110  | 150  | 10 | 753 200 837 | 2,716  | 195  | 410  | 98   | 82   | 9,5  | 6,6  |
| 180  | 90   | 150  | 10 | 753 200 881 | 2,780  | 200  | 484  | 110  | 82   | 10,7 | 5,4  |
| 180  | 110  | 150  | 10 | 753 200 150 | 4,320  | 205  | 486  | 110  | 86   | 10,7 | 6,6  |
| 180  | 160  | 150  | 10 | 753 200 882 | 5,560  | 220  | 484  | 110  | 100  | 18,7 | 9,5  |
| 200  | 63   | 200  | 10 | 753 201 873 | 6,800  | 190  | 500  | 122  | 63   | 11,9 | 3,8  |
| 200  | 90   | 200  | 10 | 753 201 874 | 6,900  | 207  | 500  | 122  | 79   | 11,9 | 5,4  |
| 200  | 110  | 200  | 10 | 753 201 875 | 5,097  | 215  | 500  | 122  | 82   | 11,9 | 6,6  |
| 200  | 160  | 200  | 10 | 753 201 876 | 7,400  | 234  | 500  | 122  | 98   | 11,9 | 9,5  |
| 225  | 75   | 200  | 10 | 753 200 839 | 7,128  | 277  | 555  | 120  | 70   | 13,4 | 4,5  |
| 225  | 90   | 200  | 10 | 753 200 840 | 4,732  | 226  | 555  | 127  | 80   | 13,4 | 5,4  |
| 225  | 110  | 200  | 10 | 753 200 841 | 4,700  | 235  | 555  | 127  | 82   | 13,4 | 6,6  |
| 225  | 160  | 200  | 10 | 753 200 842 | 5,922  | 253  | 555  | 127  | 98   | 13,4 | 9,5  |
| 225  | 180  | 200  | 10 | 753 200 843 | 7,211  | 280  | 550  | 120  | 105  | 13,4 | 10,7 |
| 250  | 110  | 250  | 10 | 753 201 878 | 8,185  | 242  | 575  | 130  | 82   | 14,8 | 6,6  |
| 250  | 160  | 250  | 10 | 753 201 879 | 9,800  | 261  | 575  | 130  | 98   | 14,8 | 9,5  |
| 315  | 110  | 300  | 10 | 753 200 851 | 15,621 | 277  | 695  | 150  | 82   | 18,7 | 6,6  |
| 315  | 160  | 300  | 10 | 753 200 852 | 12,200 | 296  | 695  | 150  | 102  | 18,7 | 9,5  |
| 315  | 200  | 300  | 10 | 753 200 152 | 17,910 | 313  | 690  | 155  | 117  | 18,7 | 11,9 |
| 315  | 225  | 300  | 10 | 753 200 153 | 16,035 | 320  | 690  | 155  | 125  | 18,7 | 13,4 |
| 315  | 250  | 300  | 10 | 753 200 854 | 15,500 | 325  | 695  | 150  | 130  | 18,7 | 14,8 |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>