



Joints SF EPDM / FKM

Exécution:

- Cleaned (washing machine), individually bagged
- Not completely silicone-free/paint-compatible (according VDMA test)
- Pour tous les collets +GF+ métriques
- Profil G-ST-P/K
- Dureté: 70°Shore **EPDM**, 75° **FKM**, 80° Shore **NBR/DUO**

d1 collets, sont les diamètres internes appropriés des collets

d (mm)	DN (mm)	PN (bar)	EPDM Code	SP	poids (kg)	FKM Code	SP	poids (kg)
16	10	16	748 441 705	0	0,007	749 441 705	0	0,007
20	15	16	748 441 706	0	0,008	749 441 706	0	0,008
25	20	16	748 441 707	1	0,011	749 441 707	1	0,019
32	25	16	748 441 708	1	0,020	749 441 708	1	0,020
40	32	16	748 441 709	1	0,015	749 441 709	1	0,018
50	40	16	748 441 710	1	0,029	749 441 710	1	0,022
63	50	16	748 441 711	1	0,046	749 441 711	1	0,055
75	65	16	748 441 712	1	0,053	749 441 712	1	0,076
90	80	16	748 441 713	1	0,063	749 441 713	1	0,086
110	100	16	748 441 714	1	0,106	749 441 714	1	0,123
125	100	16	748 441 715	1	0,158	749 441 715	1	0,158
140	125	16	748 441 716	1	0,124	749 441 716	1	0,177
160 - 180	150	16	748 441 717	1	0,147	749 441 717	1	0,153
200	200	16	748 441 719	1	0,294	749 441 719	1	0,263
225	200	16	748 441 720	1	0,174	749 441 720	1	0,181
250	250	16	748 441 721	1	0,410	749 441 721	1	0,410
280	250	16	748 441 722	1	0,226	749 441 722	1	0,226
315	300	16	748 441 723	1	0,334	749 441 723	1	0,334

d (mm)	DN (mm)	di collets (mm)	H1 (mm)	D1 (mm)	H (mm)	D (mm)
16	10	6 - 16	3	16	4	46
20	15	10 - 20	3	20	4	51
25	20	12 - 22	3	22	4	61
32	25	18 - 28	3	28	4	71
40	32	30 - 40	3	40	4	82
50	40	36 - 46	3	46	4	92
63	50	48 - 58	4	58	5	107
75	65	59 - 69	4	69	5	127
90	80	73 - 84	4	84	5	142
110	100	94 - 104	5	104	6	162
125	100	113 - 123	5	123	6	162
140	125	127 - 137	5	137	6	192
160 - 180	150	150 - 160	6	160	8	218
200	200	192 - 203	6	203	8	273
225	200	207 - 207	6	220	8	273
250	250	238 - 250	6	252	8	328
280	250	264 - 274	6	274	8	328
315	300	296 - 296	6	306	8	378

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Data sheet

valid from: 18/09/22



Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>