



Type 3519 Flow Wet-Tap Valve

Flow:

- Installs into pipe sizes: DN15 to DN900, 0.5 to 36 in
- Material: PVC body, seals FKM or EPDM
- Max Pressure rating: 7 bar @ 20 °C, (100 psi @ 68 °F)
- Standard: FKM O-rings (EPDM or FFKM on request)
- Other materials of rotor and axis on request

MFR #	Description	Pipe Size (inch)	Code
3-3519	Wet-Tap Valve only	-0	159 000 757
P51530-P3	Polypro extended length paddlewheel sensor	0.5 - 4.0	198 840 310
3-2536-P3	Polypro extended length low flow paddlewheel sensor	0.5 - 4.0	159 000 758
P51530-P4	Polypro extended length paddlewheel sensor	5.0 - 8.0	198 840 311
3-2536-P4	Polypro extended length low flow paddlewheel sensor	5.0 - 8.0	159 000 759
P51530-P5	Polypro extended length paddlewheel sensor	10.0 - 36.0	198 840 312
3-2536-P5	Polypro extended length low flow paddlewheel sensor	10.0 - 36.0	159 000 760

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>