



DEKADUR-C Rohr PVC-C grau
SDR13,6/PN16/S6,3

Ausführung:

- Material: PVC-C, hochwärmebeständig
- Abmessung: nach DIN 8079/80
- Farbe: achatgrau RAL 7038
- Rohrlänge: 5000mm, glattendig
- Attention: Pressure rates refer to operating temperatures at 20°C. Higher temperatures and aggressive flow media reduce pressure load (see above DIN and our technical documentation). Pressure load capacity has to be determined in consideration with safety demands of the respective applications and calculated in accordance.

d (mm)	SDR	PN (bar)	Code	Gewicht (kg/m)	e (mm)
32	13.6	16	163 017 133	0,379	2,4
40	13.6	16	163 017 134	0,582	3,0
50	13.6	16	163 017 135	0,896	3,7
63	13.6	16	163 017 136	1,430	4,7
75	13.6	16	163 017 137	2,020	5,6
90	13.6	16	163 017 138	2,880	6,7
110	13.6	16	163 017 139	4,270	8,1
160	13.6	16	163 017 142	8,980	11,8

Die technischen Daten sind unverbindlich. Sie gelten nicht als zugesicherte Eigenschaften oder als Beschaffenheits- oder Haltbarkeitsgarantien. Änderungen vorbehalten. Es gelten unsere Allgemeinen Verkaufsbedingungen.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Schweiz Telefon: +41 -(0)52-631 1111 E-Mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>