





ecoFIT Diaphragm valve type 514 With fusion sockets PE80 metric

Model:

- Material: PP-H/PE
- Double flow rate compared to predecessor
- One housing nut replaces four screws
- Handwheel with built-in locking mechanism
- For easy installation and removal
- Short overall length

Option:

- Individual configuration of the valve
- Self adjusting multifunctional module with integrated limit switches

d	DN	Size	PN	kv-value ($\Delta p=1$ bar)	EPDM Code	Weight (kg)	PTFE/EPDM Code	Weight (kg)
(mm)	(mm)	(inch)	(bar)	(l/min)				
20	15	½	10	125	167 514 212	0.263	167 514 232	0.371
25	20	¾	10	271	167 514 213	0.490	167 514 233	0.502
32	25	1	10	481	167 514 214	1.083	167 514 234	1.103
40	32	1 ¼	10	759	167 514 215	1.279	167 514 235	1.299
50	40	1 ½	10	1263	167 514 216	2.259	167 514 236	2.289
63	50	2	10	1728	167 514 217	2.950	167 514 237	2.978

d	D	D2	D3	L	L2	H	H1	H2	M	z	Lift = Hx	closest inch
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)		(mm)	(mm)	(inch)
20	65	65	48	128	25	73	14	12	M6	100	7	½
25	80	65	58	150	25	81	18	12	M6	118	10	¾
32	88	87	65	162	25	107	22	12	M6	126	13	1
40	101	87	79	184	45	115	26	15	M8	144	15	1 ¼
50	117	135	91	210	45	148	32	15	M8	164	19	1 ½
63	144	135	111	248	45	166	39	15	M8	194	25	2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>