

**PROGEF 标准型**  
**PP-H#气动蝶阀 243型**  
**PPA FO (常开)**  
**凸耳式 公制法兰**

**型号:**




- 总长度符合EN 558, ISO 5752标准
- 连接尺寸: ISO7005 PN10, EN1092 PN10, DIN2501 PN10
- Namur标准气源接口满足VDI/VDE 3845, 气源压力4.2 bar (60.9 psi)
- 开关时间: 90°< 1-2s
- 安装简单, 易拆卸
- 整体耐腐蚀塑料方案(气动执行器外壳材质 PP-GF)
- 带可视机械式位置指示

**选项:**

- 可选项: 位置反馈及限位开关 (限位开关需要单独采购)
- 可选配定位器RPC, RPC D, RPC PID
- 可提供其他阀门配置

**注:**

对于某些材料组合 (例如DN300阀门与PE/PP管道), 需要特殊的法兰适配器。请查看 [www.gfps.com](http://www.gfps.com) 上的“完美法兰连接工具”



d (mm)	Size (inch)	DN (mm)	PN (bar)	EPDM code	SP weight (kg)	FKM code	SP weight (kg)
63	2	50	10	199 243 832	1, 3,499	199 243 842	1, 3,499
75	2 1/2	65	10	199 243 833	1, 3,656	199 243 843	1, 3,656
90	3	80	10	199 243 834	1, 4,692	199 243 844	1, 4,692
110	4	100	10	199 243 835	1, 6,406	199 243 845	1, 6,406
140	5	125	10	199 243 836	1, 9,222	199 243 846	1, 9,222

d (mm)	Hmax (mm)	Lmax (mm)	Wmax (mm)	U (mm)	V (mm)	H4 (mm)	V1 (mm)	Lg (mm)	D2 (mm)	Q1 (mm)	Q2 (mm)	d2 (mm)	k (mm)	Y (mm)
63	338,1	245,5	165	90	133,3	23	78,8	44,7	160	40		M16	125	111
75	351,0	245,5	182	90	139,9	23	85,1	45,7	180	54	35	M16	145	111
90	367,8	343,0	210	90	145,6	23	91,2	48,7	195	67	50	M16	160	131
110	404,5	343,0	240	90	166,0	23	107,5	55,6	226	88	74	M16	180	131
140	433,7	343,0	272	90	180,0	23	122,7	63,5	258	113	97	M16	210	131

d (mm)	E (mm)	Y1 (mm)	M2 (mm)
63	119,5	15	122,75
75	119,5	15	122,75
90	141,5	15	171,50
110	141,5		171,50
140	141,5		171,50

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

# Data sheet

valid from: 2026/3/30



---

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:  
info.ps@georgfischer.com Internet: <http://www.gfps.com>