



SYGEF Standard adaptor nipple male thread R SDR21/PN16

Model:

- Avoid stresses when installing and large changes in temperature
- Material: PVDF
- With butt fusion spigot and BSP tapered male thread
- Connection to plastic thread only
- Do not use thread sealing pastes that are harmful to PVDF

d	DN	Size	PN	SDR	FM	Thread Type	Code	Weight	L	L1	s	e
(mm)	(mm)	(inch)	(bar)					(kg)	(mm)	(mm)	(mm)	(mm)
20	15	3/8	16	21	BCF, IR	R	735 910 555	0.024	50	26	32	1.9
20	15	1/2	16	21	BCF, IR	R	735 910 556	0.025	53	26	32	1.9
25	20	3/4	16	21	BCF, IR	R	735 910 557	0.035	55	26	36	1.9
32	25	1	16	21	BCF, IR	R	735 910 558	0.054	57	26	46	2.4
40	32	1 1/4	16	21	BCF, IR	R	735 910 559	0.076	60	26	55	2.4
50	40	1 1/2	16	21	BCF, IR	R	735 910 560	0.123	63	26	65	3.0
63	50	2	16	21	BCF, IR	R	735 910 561	0.166	69	27	75	3.0

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>