



Cup drill HSS carbide tipped

Model:

- Suitable for abrasive materials such as asbestos cement and cement lined (ductile) iron pipes

Inch (inch)	Description	Code	Weight (kg)
3/4	carbide tipped HSS bi-metal cutter 19,1 mm	709 810 612	0.300
7/8	carbide tipped HSS bi-metal cutter 22,2 mm	709 810 614	0.300
1	carbide tipped HSS bi-metal cutter 25,4 mm	709 810 616	0.300
1 1/8	carbide tipped HSS bi-metal cutter 28,6 mm	709 810 618	0.300
1 1/4	carbide tipped HSS bi-metal cutter 31,8 mm	709 810 620	0.300
1 3/8	carbide tipped HSS bi-metal cutter 34,9 mm	709 810 622	0.300
1 1/2	carbide tipped HSS bi-metal cutter 38,1 mm	709 810 624	0.300
1 3/4	carbide tipped HSS bi-metal cutter 44,5 mm	709 810 628	0.300
2	carbide tipped HSS bi-metal cutter 50,8 mm	709 810 632	0.300

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>