



PROGEF Standard Ball valve type 180
24V
With manual emergency override
With fusion sockets PP-H ISO

Model:

- IP68 Rating
- Factory set control range 90°<
- Heating element, position feedback (Open/Close/ Middle)
- Integrated stainless steel mounting inserts

Option:

- Other valve and actuator configurations available
- Optional accessories: Monitoring board, Positioner, Profibus DP board, Modbus TCP EA 25-250 Ethernet Interface Card

d (mm)	DN (mm)	Size (inch)	PN (bar)	kv-value ($\Delta p=1$ bar) (L/min)	EPDM Code	Weight (kg)	FKM Code	Weight (kg)
16	10	3/8	10	70	199 180 042	2.100	199 180 052	2.100
20	15	1/2	10	185	199 180 043	2.413	199 180 053	2.100
25	20	3/4	10	350	199 180 044	2.483	199 180 054	2.200
32	25	1	10	700	199 180 045	2.300	199 180 055	2.300
40	32	1 1/4	10	1000	199 180 046	2.746	199 180 056	2.600
50	40	1 1/2	10	1600	199 180 047	3.555	199 180 057	3.000
63	50	2	10	3100	199 180 048	3.447	199 180 058	3.460
75	65	2 1/2	10	5000	199 180 049	6.200	199 180 059	6.200
90	80	3	10	7000	199 180 050	7.200	199 180 060	7.200
110	100	4	10	11000	199 180 051	11.200	199 180 061	11.200

d (mm)	DE1 (mm)	E (mm)	G (mm)	H (mm)	H1 (mm)	H4 (mm)	Lz (mm)	M (mm)	M1 (mm)	M2 (mm)	L (mm)	L1 (mm)	z (mm)	Actuator	B3 (mm)
16	50	122	M6	227	27	12	28	180	97	83	93	33	67	EA25	25
20	50	122	M6	227	27	12	28	180	97	83	95	33	68	EA25	25
25	58	122	M6	231	30	12	33	180	97	83	109	33	77	EA25	25
32	68	122	M6	237	36	12	36	180	97	83	119	33	83	EA25	25
40	84	122	M8	243	44	15	43	180	97	83	135	33	99	EA25	45
50	97	122	M8	249	51	15	45	180	97	83	147	33	105	EA25	45
63	124	122	M8	264	64	15	51	180	97	83	168	33	117	EA25	45
75	166	122	M8	313	85	15	68	180	98	82	233	33	167	EA45	70
90	200	122	M8	325	105	15	71	180	98	82	254	33	180	EA45	70
110	238	122	M12	363	123	22	82	180	98	82	301	33	215	EA120	120

Data sheet

valid from: 2/8/25



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>