




JRGURED Druckminderer Rotguss

- Temperatur: max. 30°C
- Werkstoff: Rotguss, Edelstahl, EPDM, Kunststoff
- Auslieferungszustand: 400 kPa (4 bar)
- Sekundärdruck: 200 - 600 kPa (2 - 6 bar)
- Anschluss: Manometer
- Bestehend aus: Verschraubungen
- *Auslauf mit Ersatz

	DN (mm)	GN (inch)	Zoll (inch)	JRG Code	NPK	GF Code	NPK	SP	Gewicht (kg)
*	15	½	½	1300.240		350 731 001		1	0.742
*	20	¾	¾	1300.320		350 731 101		1	0.970
*	25	1	1	1300.400		350 731 201		1	1.600
*	32	1 ¼	1 ¼	1300.480		350 731 301		1	2.423
	40	1 ½	1 ½	1300.560		350 731 401		1	4.050
	50	2	2	1300.640		350 731 501		1	6.425
	65	2 ½	2 ½	1300.720		350 734 601		1	7.300

	DN (mm)	GN (inch)	d1 R (inch)	d2 G (inch)	d3 Rp (inch)	d4 (mm)	h1 (mm)	h2 (mm)	l1 (mm)	l2 (mm)	PN (bar)	z (mm)	○ (mm)
*	15	½	½	¾	⅝	54	34	79	130	25	25	40	5
*	20	¾	¾	1	⅝	60	42	86	142	29	25	43	5
*	25	1	1	1 ¼	¾	72	52	110	167	34	25	50	6
*	32	1 ¼	1 ¼	1 ½	¾	80	64	121	196	38	25	60	6
	40	1 ½	1 ½	1 ¾	¾	96	80	157	222	39	25	73	8
	50	2	2	2 ¾	¾	105	98	172	268	47	25	88	8
	65	2 ½	2 ½	3	¾	105	98	172	292	56	25	90	8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>