



3-Way ball valve type 543 Pro P PVC-U

Horizontal/L-port

FC (Fail safe to close)

Without manual override

With solvent cement spigots metric

Model:

- Control pressure supply through integrated NAMUR interface according VDI/VDE 3845 with 5.6 bar (81.2 psi)
- Basic position B-C opened, activated position A-C opened, see flow scheme
- Control time 90° < 1-2s
- For easy installation and removal
- Integrated stainless steel mounting inserts
- Full plastic solution (actuator housing made of PP-GF)
- Visual position indicator
- Z-dimension, valve end and union nut are compatible with types 285 – 288 and 543 (1st Generation)

Option:

- Position feedback sensor, incl. LED feedback (DN10-50) - PNP, NPN and NAMUR
- Positioner RPC, RPC D, RPC PID
- Individual configuration of the valve

d	DN	Size	PN	kv-value	EPDM	SP	Weight	FKM	SP	Weight
(mm)	(mm)	(inch)	(bar)	(Δp=1 bar)	Code		(kg)	Code		(kg)
16	10	3/8	10	50	199 295 002	1	1.121	199 295 012	1	1.121
20	15	1/2	10	75	199 295 003	1	1.130	199 295 013	1	1.130
25	20	3/4	10	150	199 295 004	1	1.241	199 295 014	1	1.264
32	25	1	10	280	199 295 005	1	1.463	199 295 015	1	1.436
40	32	1 1/4	10	480	199 295 006	1	2.560	199 295 016	1	2.560
50	40	1 1/2	10	620	199 295 007	1	3.054	199 295 017	1	3.054
63	50	2	10	1230	199 295 008	1	4.478	199 295 018	1	4.451

d	Actuator	D	H	H1	H2	H3	H4	H5	H6	L	L1	L2	L3	L4	L6
(mm)		(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
16	PPA08	50	157	28	62	95	41	75	8	131	159	73	36	25	74
20	PPA08	50	157	28	62	95	41	75	8	141	159	73	36	25	74
25	PPA15	58	179	32	71	108	45	88	8	165	211	86	43	25	94
32	PPA15	68	179	36	71	108	45	88	8	182	211	99	50	25	94
40	PPA40	84	215	45	84	131	56	111	9	209	246	120	60	45	120
50	PPA40	97	215	51	84	131	56	111	9	242	246	137	69	45	120
63	PPA40	124	237	65	106	131	56	111	9	302	246	179	89	45	120

d	L7	M	closest
(mm)	(mm)		inch
16	32	6	3/8
20	32	6	1/2
25	38	6	3/4
32	38	6	1
40	47	8	1 1/4
50	47	8	1 1/2
63	47	8	2

Data sheet

valid from: 4/3/25



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>