



CONTAIN-IT Plus Mechanical connection PP-H/PE100 Connections for socket fusion

Model:

- Protective housing PVC-U PN6 / sealing according to inner pipe
- For easy installation and removal
- With union PP-H

d (mm)	D (mm)	PN (bar)	PN (Outer Pipe) (bar)	SDR	EPDM Code	Weight (kg)	FKM Code	Weight (kg)
20	50	10	6	11	727 240 106	3.924	727 240 126	3.924
25	50	10	6	11	727 240 107	3.896	727 240 127	3.896
32	63	10	6	11	727 240 108	6.160	727 240 128	6.160
40	75	10	6	11	727 240 109	9.880	727 240 129	9.880
50	90	10	6	11	727 240 110	11.506	727 240 130	11.506
63	110	10	6	11	727 240 111	9.811	727 240 131	9.811

d (mm)	D1 (mm)	ZA 1 (mm)	ZA 2 (mm)	Zi 1 (mm)	Zi 2 (mm)	H (mm)	H2 (mm)
20	66	255	330	287	329	92	85
25	66	255	330	289	327	92	85
32	81	275	355	311	350	104	105
40	97	325	410	364	403	119	123
50	118	340	425	382	415	119	123
63	139	350	480	398	466	119	123

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>