

Robinet à membrane, type 317, PVDF-Standard avec brides PP-V, ANSI

Exécution:

- **matière:** PVDF
- DN15-65 with backing flange
- DN80-150 with fixed flange
- **longueur selon EN 558-1**
- membrane en PTFE avec membrane d'appui en EPDM (conforme FDA)


Option:

- volant verrouillable (version standard non verrouillable)
- * **DN80 and DN150 fixed flanges metric and Inch ANSI B16.5**


	d (mm)	Pouces (inch)	DN (mm)	PN (bar)	valeur kv (Δp=1 bar) (l/min)	PTFE with EPDM supp. diaphragm Code	poids (kg)
	75	2 ½	65	10	992	175 317 538	5,718
*	90	3	80	10	1700	175 317 009	10,760
	110	4	100	6	2700	175 317 340	15,406
*	160	6	150	6	6033	175 317 012	31,500

	d (mm)	Pouces (inch)	DN (mm)	PN (bar)	D (mm)	D1 (mm)	D2 (mm)	D3 (mm)	H (mm)	H1 (mm)	H2 (mm)	L (mm)	L1 (mm)	L2 (mm)	L3 (mm)
	75	2 ½	65	10	185	140	152	18	201	46	15	290			70
*	90	3	80	10	200	160	270	18	265	57	23	310	35	120	
	110	4	100	6	225	191	270	19	304	69	23	350	35	120	
*	160	6	150	6	285	240	400	22	437	108	23	480	26	100	200


	d (mm)	Pouces (inch)	DN (mm)	PN (bar)	M	Course = Hx (mm)	AL
	75	2 ½	65	10	M8	30	4
*	90	3	80	10	M12	40	8
	110	4	100	6	M12	50	8
*	160	6	150	6	M12	70	8



DN 15-65



DN 80-100



DN 150

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>