





Tapping saddle 自鑽鞍座 (附鑽刀) Monobloc version

- 10 bar Gas / 16 bar Water
- With integrated cutter to tap live mains under pressure
- Complete with moulded-on lower part
- 4 mm pin connectors
- Limited path fusion indicators
- Long fusion outlet
- O-ring-sealed screw cap



d	Do3	DN	PN	code	weight	L3	L4	Db	W	H	H4	SDR pipe
(mm)	(mm)	(mm)	(bar)		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	
63	20	50	16	193 131 932	0,368	110	76	25	144	146	44	9 - 11
63	25	50	16	193 131 933	0,393	110	76	25	144	146	44	9 - 11
63	32	50	16	193 131 934	0,376	110	76	25	144	146	44	9 - 11
90	20	80	16	193 131 952	0,494	115	76	32	162	198	61	9 - 17.6
90	25	80	16	193 131 953	0,503	115	76	32	162	198	61	9 - 17.6
90	32	80	16	193 131 954	0,505	115	76	32	162	198	61	9 - 17.6
90	63	80	16	193 131 957	0,667	115	76	32	162	198	61	9 - 17.6
110	20	100	16	193 131 962	0,560	115	76	32	162	208	71	9 - 17.6
110	25	100	16	193 131 963	0,570	115	76	32	162	208	71	9 - 17.6
110	32	100	16	193 131 964	0,574	125	76	32	162	208	71	9 - 17.6
110	63	100	16	193 131 967	0,684	160	100	32	162	208	71	9 - 17.6
125	20	100	16	193 131 972	0,562	120	76	32	162	216	79	9 - 17.6
125	25	100	16	193 131 973	0,552	120	76	32	162	216	79	9 - 17.6
125	32	100	16	193 131 974	0,574	120	76	32	162	216	79	9 - 17.6
125	63	100	16	193 131 977	0,704	120	76	32	162	216	79	9 - 17.6
160	20	150	16	193 131 992	0,631	120	76	32	162	233	96	11 - 17.6
160	25	150	16	193 131 993	0,641	125	76	32	162	233	96	11 - 17.6
160	32	150	16	193 131 994	0,648	130	76	32	162	233	96	11 - 17.6
160	63	150	16	193 131 997	0,794	170	100	32	162	233	96	11 - 17.6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>