



**PROGEF Standard**  
**Valve end 546 Pro and 543 Pro (G34)**  
**With threaded socket NPT reinforced**

**Model:**

- Material: PP-H
- Connection to plastic or metal threads
- Reinforcing ring stainless (A2)
- Do not use thread sealing pastes that are harmful to PP

NPT (inch)	PN (bar)	Code	Weight (kg)	D (mm)	D1 (mm)	L (mm)	L1 (mm)	z (mm)
3/8	16	<b>167 482 966</b>	0.008	38	26	20	4	7
1/2	16	<b>167 482 967</b>	0.012	38	33	21	4	4
3/4	16	<b>167 482 968</b>	0.016	44	39	23	5	5
1	16	<b>167 482 969</b>	0.027	53	47	28	5	6
1 1/4	16	<b>167 482 970</b>	0.037	65	57	31	5	7
1 1/2	16	<b>167 482 971</b>	0.052	77	65	34	6	11
2	16	<b>167 482 972</b>	0.091	99	77	41	7	17

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>