



Quick Connect Valve 700 (QC7) Swiveled end-connection: PP-H/PVDF Spigot (Infrared fusion)

The QC7 utilizing two full bore ball valves that only allow flow when both valves are open. The patented interlock design ensures that the valve cannot be disconnected while it is under pressure.

Model:

- Dual interlock lever mechanism
- 360° swiveled end-connections
- Color coding: Blue for supply // Red for return
- Fluid loss: Approx 5,5cc.
- Valve body: PVDF
- Sealing: EPDM

	DN (mm)	Size (inch)	e (mm)	d (mm)	DE (mm)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)	Cv 100 (gal/min)
Spigot PVDF - Blue	25	1	2.4	32	70	10	570	39
Spigot PVDF - Red	25	1	2.4	32	70	10	570	39
Spigot PP-H - Blue	25	1	2.9	32	70	10	570	39
Spigot PP-H - Red	25	1	2.9	32	70	10	570	39

	DN (mm)	EPDM Code	SP	Weight (kg)
Spigot PVDF - Blue	25	735 911 705	1	0.370
Spigot PVDF - Red	25	735 911 707	1	0.370
Spigot PP-H - Blue	25	735 911 709	1	0.332
Spigot PP-H - Red	25	735 911 711	1	0.332

	DN (mm)	L1 (mm)	M1-1 (mm)	M2-1 (mm)	Lmax (mm)	Hmax (mm)	Wopen (mm)	Wclosed (mm)
Spigot PVDF - Blue	25	118	26.5	46	131	85.5	79.5	85.5
Spigot PVDF - Red	25	118	26.5	46	131	85.5	79.5	85.5
Spigot PP-H - Blue	25	118	26.5	46	131	85.5	79.5	85.5
Spigot PP-H - Red	25	228	26.5	46	131	85.5	79.5	85.5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>