



ecoFIT Segmented Cross Tee Equal PE100 SDR13.6

Model:

- Long spigot for butt- and electrofusion welding
- Application: Water distribution
- Production process: segment welded
- **Derating factor 0.5 as per ISO 4427-3**
- Pressure rating: 6.3 bar water

Note:

* Please call us for availability

d (mm)	Code	Weight (kg)	z (mm)	z1 (mm)	L (mm)	e (mm)
90	P2315127090	1.34	450	225	180	6.7
110	P2315127110	2.63	590	295	240	8.1
125	P2315127125	3.43	605	303	240	9.2
140	P2315127140	4.35	620	310	240	10.3
160	P2315127160	5.78	640	320	240	11.8
180	P2315127180	7.44	660	330	240	13.3
200	P2315127200	9.28	680	340	240	14.7
225	P2315127225	12.00	705	353	240	16.6
250	P2315127250	18.14	850	425	300	18.4
280	P2315127280	23.15	880	440	300	20.6
315	P2315127315	38.13	1115	558	400	23.2
355	P2315127355	49.20	1155	578	400	26.1
400	P2315127400	63.66	1200	600	400	29.4
450	P2315127450	82.33	1250	625	400	33.1
500	P2315127500	114.15	1400	700	450	36.8
630	P2315127630	222.46	1730	865	550	46.3
710	P2315127710	289.47	1810	905	550	52.2
800	P2315127800	456.40	2200	1100	700	58.8
900	P2315127900	625.20	2400	1200	750	66.1
*	P2315127001	778.06	2500	1250	750	73.5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:

info.ps@georgfischer.com Internet: <http://www.gfps.com>