



PROGEF Plus 3-Way ball valve type 543 Pro silicone free
Horizontal/L-port
With fusion sockets metric

Model:

- Material: PP-H / silicone free cleaned
- Lockable lever as standard (DN10-DN50)
- For easy installation and removal (valve end and union nut are compatible with type 546)
- Ball seals PVDF
- Angle of operation 360° without turn limiter
- Turn limiter 90° enclosed, in different positions usable as a clip-on ring
- Integrated stainless steel mounting inserts
- Delivery status A-C opened, see flow scheme
- Z-dimension, valve end and union nut are compatible with type 543 (1stGeneration)

Option:

- Interface-module with position feedback sensor, incl. LED feedback (DN10-50)
- Manual spring return lever ("Dead man") (DN10-25)
- Pneumatic or electric actuators from GF
- Individual configuration of the valve possible

d	DN	PN	kv-value	EPDM	SP	Weight	FKM	SP	Weight
(mm)	(mm)	(bar)	($\Delta p=1$ bar)	Code		(kg)	Code		(kg)
			(l/min)						
16	10	10	50	167 543 401	1	0.161	167 543 411	1	0.161
20	15	10	75	167 543 402	1	0.165	167 543 412	1	0.172
25	20	10	150	167 543 403	1	0.237	167 543 413	1	0.237
32	25	10	280	167 543 404	1	0.361	167 543 414	1	0.361
40	32	10	480	167 543 405	1	0.616	167 543 415	1	0.616
50	40	10	620	167 543 406	1	0.912	167 543 416	1	0.912
63	50	10	1230	167 543 407	1	1.773	167 543 417	1	1.773

d	D	H	H1	H2	L	L1	L2	L3	L4	L5	L6	M	z	z1	closest
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)		(mm)	(mm)	inch
															(inch)
16	50	61	28	8	110	82	72	36	25	35	47	6	82	41	$\frac{3}{8}$
20	50	61	28	8	112	82	72	36	25	35	47	6	82	41	$\frac{1}{2}$
25	58	74	32	8	129	106	85	43	25	44	62	6	97	49	$\frac{3}{4}$
32	68	80	36	8	146	106	98	49	25	44	62	6	110	55	1
40	84	95	45	9	170	131	118	59	45	57	74	8	132	66	1 $\frac{1}{4}$
50	97	102	51	9	193	131	135	68	45	57	74	8	151	76	1 $\frac{1}{2}$
63	124	117	65	9	244	152	176	88	45	66	86	8	188	94	2

Data sheet

valid from: 4/3/25



Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>