



ELGEF Plus Tapping saddle PE100
d40-63mm / SDR11 / Monobloc version / With gas-stop type AD UE

- **PE 100 SDR 11** (ISO S5)
- 1 bar Gas (for pressures from **25 mbar to 1 bar**)
- With integrated cutter to tap live mains under pressure
- Gas-Stop System Pipelife Type AD (GS 32/25 UE)
- **With overflow orifice**
- Set comes with Gas-Stop pre-assembled
- Installation instructions of Gas-Stop manufacturer are to be observed
- Complete with lower part
- 4 mm pin connectors
- Limited path fusion indicators
- Long fusion outlet
- O-ring-sealed screw cap

d	SDR	DN	d1	SDR pipe	Code	SP	Weight
(mm)		(mm)	(mm)				(kg)
40	11	32	32	9 - 11	193 130 614	6	0.290
50	11	40	32	9 - 11	193 130 624	6	0.283
63	11	50	32	9 - 17.6	193 130 634	1	0.446

d2	H	H1	L	L1	z	Vn max
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(m ³ /h)
16	99	33	103	76	120	10
16	104	38	103	76	120	10
25	134	44	126	76	130	10

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
 info.ps@georgfischer.com Internet: <http://www.gfps.com>