



Metal transition coupling male

- installation without disassembling
- suitable for PE and PEX pipes
- water PN16
- material: PP / brass
- gasket: EPDM quality for drinkable water
- male thread: ISO 7 (conical) brass
- Metal insert with hexagon starting from R 1 1/4
- colour: blue-black

d	R	Code	SP	Weight	D	L	l3	l1	l2
(mm)	(inch)			(kg)	(mm)	(mm)	(mm)	(mm)	(mm)
20	1/2	158 400 281	50	0.112	45	100.6	14.7	54	19
25	3/4	158 400 282	25	0.166	53	108.9	15.0	59	21
32	3/4	158 400 283	18	0.201	64	117.2	15.0	66	23
32	1	158 400 284	18	0.272	64	122.7	17.0	66	23
32	1 1/4	158 400 285	14	0.526	64	136.1	19.0	66	23
32	1 1/2	158 400 286	12	0.552	64	139.4	20.0	66	23
40	1	158 400 287	12	0.341	75	138.2	17.0	76	26
40	1 1/4	158 400 288	12	0.547	75	143.9	19.0	76	26
40	1 1/2	158 400 289	12	0.576	75	147.2	20.0	76	26
40	2	158 400 290	6	0.810	75	160.8	25.0	76	26
50	1 1/4	158 400 291	6	0.705	97	157.1	19.0	88	30
50	1 1/2	158 400 292	6	0.733	97	160.4	20.0	88	30
63	1 1/2	158 400 293	3	0.991	114	180.5	20.0	104	35
63	2	158 400 294	3	1.156	114	190.5	25.0	104	35

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>