Data sheet

valid from: 8/20/24





Plastic pipe cutter PEcut 1200

- Plastic pipe cutter for precise and safe cutting of plastic pipes
- Battery powered, oil-free chain saw with unique clamping guiding mechanism
- Application range for HDPE pipes = 250mm to 1200mm (10" to 46")
- Application range for COOL-FIT pipes, d160/D250mm up to d450/D630mm
- Wall thickness cutting range = 10mm to 180mm
- Recommended for PE pipes and pre-insulated COOL-FIT PE pipes
- Recommended for pipe materials HDPE and PP
- Maximum axial space required = 37 cm
- Minimum radial space required = 35 cm
- Scope of delivery:
- Please observe the description to select the country-specific variant
- Cordless, Battery powered
- Support wagon
- 3 roller assemblies, 2 tension belts, and 2 quick links
- Includes 2 batteries, CAS 5.5Ah, and 1 Charging Unit 12/18V
- Transportation case included (665mm x 562mm x 250mm)

d	d1	Code	weight	Description	L	В	H
(mm)	(mm)		(kg)		(mm)	(mm)	(mm)
250	1200	799 198 150	19.70	PEcut 1200-230V, Charger LG12/18V	665	562	250
250	1200	799 198 151	19.70	PEcut 1200-115V US, Charger LG12/18V US	665	562	250
250	1200	799 198 152	19.70	PEcut 1200-230V UK, Charger LG12/18V UK	665	562	250

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com