



Gauge guard type Z500/501 PVC-U

Z500 with manometer, Z501 without manometer

Model:

- Connections spigots with inner thread: d25 with G 1/4" and d32 with G 1/2"

d (mm)	D (mm)	Type	Manometer	PN (bar)	PTFE Code	SP	Weight (kg)
25		501	no	10	199 042 000	1	0.144
32		501	no	10	199 042 001	1	0.261
25	63	500	yes	10	199 042 010	1	0.271
32	100	500	yes	10	199 042 011	1	0.633
25	63	500	yes	10	199 042 020	1	0.500
25	63	500	yes	10	199 042 030	1	0.267
32	100	500	yes	10	199 042 031	1	0.657
32	63	500	yes	10	199 042 040	1	0.400

d (mm)	Wetted Sensor Body Material	Sensor Housing Material	Sensor Type	Material	Manometer connection (inch)	Pressure range (bar)
25	PTFE, PVC-U		Analog		G 1/4"	
32	PTFE, PVC-U		Analog		G 1/2"	
25	PTFE, PVC-U	Brass, ABS	Analog	brass	G 1/4"	0 - 10
32	PTFE, PVC-U	Brass, ABS	Analog	brass	G 1/2"	0 - 10
25	PTFE, PVC-U	SS 316	Analog	steel	G 1/4"	0 - 10
25	PTFE, PVC-U	Brass, ABS	Analog	brass	G 1/4"	0 - 6
32	PTFE, PVC-U	Brass, ABS	Analog	brass	G 1/2"	0 - 6
32	PTFE, PVC-U	SS 316	Analog	steel	G 1/2"	0 - 6

d (mm)	Pressure range (psi)
25	
32	
25	0.00 - 145.03
32	0.00 - 145.03
25	0.00 - 145.03
25	0.00 - 87.02
32	0.00 - 87.02
32	0.00 - 87.02

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>