



ecoFIT installation fitting type 318 PE100 For butt fusion systems metric SDR 11

Attention:

- sensor length depends on installation fitting

Model:

- Threaded outlet 1 1/4" NPSM
- Union end with butt fusion spigot PE100
- Body and union nut PP-H

Range of use:

- Compatible Signet pH/ORP sensors: type 2724, 2725, 2726, 2734, 2736, 2735
- Compatible Signet flow sensors: type 2551, 2537, 515, 8510, 2536, 8512

d	DN	PN	SDR	FM	EPDM	Weight	FKM
(mm)	(mm)	(bar)			Code	(kg)	Code
20	15	10	11	IR	753 318 006	0.136	753 318 036
25	20	10	11	IR	753 318 007	0.190	753 318 037
32	25	10	11	IR	753 318 008	0.250	753 318 038
40	32	10	11	IR	753 318 009	0.356	753 318 039
50	40	10	11	IR	753 318 010	0.510	753 318 040
63	50	10	11	IR	753 318 011	0.800	753 318 041

d	D	z	L	L1	L2	H	e	Sensor Type
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	
20	48	112	224	90	52	76	1.9	X0 (DN15 – DN100, 1/2" to 4")
25	58	121	242	100	53	78	2.3	X0 (DN15 – DN100, 1/2" to 4")
32	65	128	256	110	55	81	2.9	X0 (DN15 – DN100, 1/2" to 4")
40	79	136	272	110	60	85	3.7	X0 (DN15 – DN100, 1/2" to 4")
50	91	147	294	120	66	89	4.6	X0 (DN15 – DN100, 1/2" to 4")
63	105	158	316	130	70	95	5.8	X0 (DN15 – DN100, 1/2" to 4")

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>