



ecoFIT Segmented Bend 1.5D 90° PE100 SDR13.6

Model:

- Long spigot for butt- and electrofusion welding
- Application: Water distribution
- Production process: segment welded
- **Derating factor 0.8 as per ISO 4427-3**
- Pressure rating: 10 bar water

Note:

Please call us for availability

d (mm)	Code	Weight (kg/m)	Z (mm)	L (mm)	R (mm)	e (mm)
90	P2315607090	1.08	348	150	198.0	6.7
110	P2315607110	2.00	420	200	220.0	8.1
125	P2315607125	2.57	425	200	225.0	9.2
140	P2315607140	3.22	424	200	224.0	10.3
160	P2315607160	4.37	448	200	240.0	11.8
180	P2315607180	5.89	473	200	270.0	13.3
200	P2315607200	7.66	502	200	300.0	14.7
225	P2315607225	10.29	537	200	337.5	16.6
250	P2315607250	14.99	622	250	375.0	18.4
280	P2315607280	19.81	663	250	420.0	20.6
315	P2315607315	31.38	821	350	472.5	23.2
355	P2315607355	42.26	883	350	532.5	26.1
400	P2315607400	57.42	950	350	600.0	29.4
450	P2315607450	78.02	1025	350	675.0	33.1
500	P2315607500	108.78	1150	400	750.0	36.8
560	P2315607560	145.33	1240	400	840.0	41.2
630	P2315607630	206.98	1395	450	945.0	46.3
710	P2315607710	295.84	1565	500	1065.0	52.2
800	P2315607800	444.74	1850	650	1200.0	58.8
900	P2315607900	623.29	2050	700	1350.0	66.1
*	1000 P2315607001	814.91	2200	700	1500.0	73.5
*	1200 P2315607002	1505.41	2500	700	1800.0	88.2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>