



ABS valve end 546 Pro and 543 Pro (G23)
With threaded socket Rp reinforced

Model:

- Connection to plastic or metal threads
- Reinforcing ring stainless (A2)
- Do not use thread sealing pastes that are harmful to ABS

Rp	PN	Code	SP	Weight	D	D1	L	L1	z
(inch)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)	(mm)
3/8	16	169 480 925		0.008	38	24	20	4	7
1/2	16	169 480 926		0.010	38	28	22	4	6
3/4	16	169 480 927		0.014	44	34	25	5	7
1	16	169 480 928		0.023	53	42	28	5	7
1 1/4	16	169 480 929		0.035	65	52	30	5	7
1 1/2	16	169 480 930		0.077	77	63	32	6	9
2	16	169 480 931		0.130	99	78	38	7	10

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>